

# Leviat

A CRH COMPANY

## **Product Health and Safety Data Sheets**

### **Product:**

Austenitic Stainless Steel Building Components. (Including Angles, Lintels, Reinforcing Bars, Special Fabrications and Wall Ties).

### **Material Analysis:**

Various grades of Austenitic Stainless Steel, as listed below, are used.

% MAXIMUM CONTENT									
Grade	C	Si	Mn	P	S	Cr	Mo	Ni	Other
<b>304</b>	0.08	1.00	2.00	0.045	0.030	18.0/20.0	----	8.00/10.5	----
<b>304L</b>	0.03	1.00	2.00	0.045	0.030	18.0/20.0	----	8.00/10.5	----
<b>316</b>	0.08	1.00	2.00	0.045	0.030	16.0/18.0	2.00/3.00	10.0/14.0	----
<b>316L</b>	0.03	1.00	2.00	0.045	0.030	16.0/18.0	2.00/3.00	10.0/14.0	----
<b>321</b>	0.08	1.00	2.00	0.045	0.030	17.0/19.0	----	9.00/12.0	Ti 5 x Cmin
<b>310</b>	0.15	1.50	2.50	0.045	0.030	25.0/28.0	----	20.0/22.5	----
<b>320</b>	0.08	1.50	2.50	0.045	0.030	16.0/18.0	2.00/3.00	10.0/14.0	Ti 5 x Cmin

### **Hazards**

When handling the product, there is a risk of laceration of the skin. Injury, including skin laceration and eye injury may occur when breaking open the strapping due to release of tension.

When subjected to elevated temperatures, e.g. during welding or flame cutting, fumes are produced containing oxides of iron and the added elements. The principal mode of entry into the body is inhalation and the potential effects on health, which include metal fume fever, a short lasting condition with symptoms similar to those of influenza, are dealt with in the documents listed under "Some Relevant References".

### **Precautionary and Proactive Methods**

When handling the product appropriate protective clothing should be worn to prevent lacerations. Similarly, when breaking open the strapping appropriate clothing and equipment such as hand and eye protection should be worn.

To ensure the Occupational Exposure Limits set out over-leaf are not exceeded when fume/dust is generated provide adequate ventilation, if necessary, including local fume extraction.

Alternatively, where necessary, appropriate respiratory protective equipment should be provided for use by those at risk from inhalation of fumes.

## **Product Health and Safety**

### **Data Sheets continued**

#### **Current Occupational Exposure Limits**

	<b>Type of Limit</b>	<b>8h.TWA</b>	<b>15Min.TWA</b>
Iron Oxide, fume (as Fe)	OES	5.0mg/m <sup>3</sup>	10.0mg/m <sup>3</sup>
Manganese and its inorganic compounds (as Mn)	OES	0.2 mg/m <sup>3</sup> (Inhalable) 0.05 mg/m <sup>3</sup> (Respirable)	-
Chromium metal 'bi' and 'tri'valent (as Cr)	OES	0.5mg/m <sup>3</sup>	-
Chromium hexavalent (as Cr)	MEL	0.01mg/m <sup>3</sup> 0.025 mg/m <sup>3</sup> (process generated)	-
Nickel compounds (as Ni), soluble compounds	MEL	0.1mg/m <sup>3</sup>	-
Nickel compounds (as Ni), insoluble compounds	MEL	0.5mg/m <sup>3</sup>	-
Molybdenum compounds (as Mo), soluble compounds	OES	5.0mg/m <sup>3</sup>	10.0mg/m <sup>3</sup>
Molybdenum compounds (as Mo), insoluble compounds	OES	10.0mg/m <sup>3</sup>	20.0mg/m <sup>3</sup>
Vanadium Pentoxide	MEL	0.05mg/m <sup>3</sup>	-

#### **Some Relevant References**

Personal Protective Equipment at Work Regulations 1992

BS EN 166:2002 – Personal Eye Protection Specifications

#### **HSE Guidance Notes**

EH2: Chromium – Health Surveillance for Hexavalent Chromium Compounds

EH40: Occupational Exposure Limits – current edition

HSG173: Monitoring Strategies for Toxic Substances

WL3: Welding Fume Control

INDG351: Working with Nickel – Are you at risk?

All information and references in these data sheets are accurate as of November 2020. Users/customers should ensure that there have been no alterations or further data sheets since that date.

**If you require further information or advice on the use of this product, please consult our Technical Department.**